## USB 3.0 Panel Mount Cable, A female with screws to A female, UL, 25cm

Product number U3-A-25-UL Length 250mm



## Product description

USB 3.0 Panel Mount Cable for industrial applications: USB A female (mountable with 2 screws) to USB A female, UL 20276 cable material, length: about 25cm, screws included

## **Key features**

- Short USB 3.0 panel mounting cable with screw-on A socket
- SPECIAL FEATURE: socket/socket version
- SPECIAL FEATURE: UL 20276 cable material (e.g. from E340033 80°C 30V VW-1)
- with UL ideal for exports
- Connection 1: USB 3.0 A panel-mount socket (female, recessed nuts on the side)
- Connection 2: USB 3.0 A socket (female)
- scope of delivery: Cable incl. 2 screws (screw type UNC 4-40, length approx. 15mm)
- screw spacing / hole spacing: 25mm
- double-shielded cable (foil shield and braided shield)
- · data wires twisted pair
- wire gauges: 28 AWG/1P and 24 AWG/2C
- conductor material: copper (CU)
- USB 2.0 compatible + downward compatible with USB 1.1
- suitable for 480 MBit/s (high speed), 12 MBit/s (full speed) and 1.5 MBit/s (low speed)
- · colour: black
- length: about 0.25 metres | 25cm
- customs tariff no.: 85444290
- e.g. for industrial applications, rear panel brackets, internal USB extensions
- · CE, WEEE, RoHS compliant

## More images









