# USB 3.2 Gen.2x2 cable with 2x Type-C<sup>™</sup> male 20Gbps 5A 1m

Product number HX-C22-10 Length 1000mm



# Product description

USB 3.2 Gen.2x2 cable with 2x Type-C<sup>™</sup> male, data transfer rates up to 20Gbps (dual lane), Power Delivery up to a charging current of 5 Ampere, 1m

## **Highlights**

- up to 20 Gbps speed (dual lane)
- USB Power Delivery 5A
- USB 3.2 Gen 2x2 is twice as fast as USB 3.2 Gen 2 (10 Gbps)

#### **Technical details**

- short USB 3.2 Gen 2x2 connection cable
- Type C connector (Type-C™) on both sides, male
- Length: 1m
- suitable for data transfer rates up to 20 Gbps (dual lane)
- supports USB Power Delivery up to a charging current of 5 amps (at max. 20V = 100W)
- in accordance with IEC 62680-1-3:2021 standard
- Quality: PREMIUM
- UL cable material (e.g. E340033)
- Data AWG32, Power AWG22 (copper, CU)
- twisted wire pairs
- triple shielding (braiding + foils)
- shielded connectors
- video signals up to 3840x2160 (60Hz) are supported
- cable diameter approx. 4.5±0.2mm
- can be used as a data cable and charging cable
- · colour: black

### **Environmental protection \***

www.partsdata.de www.partsdata.eu www.partsdata.fr

- RoHS-compliant: Product complies with EU environmental protection directives 2011/65/EU and RoHS 2015/86 ("Restriction of Hazardous Substances")
- WEEE compliant (DE65810611): Waste of Electrical and Electronic Equipment The WEEE directive regarding recycling and reutilisation makes a significant contribution to environmental protection.
- REACH-compliant procurement process ("Registration Evaluation Authorisation and Restriction of Chemicals")
- Product packaging made of cardboard (no plastic)
- CE: all European standards are complied with

\*All information on environmental protection is based on information provided by the manufacturer/supplier.

www.partsdata.de www.partsdata.eu www.partsdata.fr

# More images



# **PINOUT**







