

Mountable USB cable Af Am right angled DOWN 50cm

Product number CU-VD-05

Length 500mm



Product description

Mountable USB cable for industrial applications, plug type A (male, 90° angled DOWN) to type A female (mountable with 2 screws), 50cm, double shielded, twisted pair, for USB 1.1 und USB 2.0 (up 480 MBit/s)

Specifications

- USB 2.0 panel mount cable | USB 2.0 rear cable
- 1st connector: *mountable* USB 2.0 type A female *with screws*
- the molded screw-style A connector enables easy connection to a faceplate or machined port
- screw distance (mountable female side): 26mm
- 2nd connector: USB 2.0 type A male **angled 90° DOWN as a space-saving solution**
- PREMIUM cable quality
- double shielded: foil and braid shielding reduces EMI-RFI interference
- copper wires: 28 AWG/1P (data, twisted pair), 24 AWG/2C (5V)
- the twisted pair construction helps to reduce crosstalk thus ensuring high speed and error-free data transfer
- UL cable material E238846 UL AWM 2725 80°C 30V VW-1 28AWG/1P 24AWG/2C
- cable diameter approx. 5mm
- USB 2.0 compliant and backwards compliant USB 1.1
- supports USB 2.0 High Speed 480 Mbps, USB 1.1 Full Speed 12 Mbps, USB-1.1 Low Speed 1.5 Mbps
- 2 screws included (pre-assembled), screw type UNC 4/40
- RoHS compliant
- customs tariff n°: 85444290
- colour: black
- e.g. for industrial applications, rear panel brackets, internal USB extensions

More images





